

TECHNICAL DATA SHEET PanoReserve

Reference/Strap 1-65-01-26-12-30 (Louisiana Alligator nubuck leather strap blue)

1-65-01-26-12-35 (calf skin leather strap blue)

1-65-01-26-12-70 (stainless steel bracelet)

Case materialstainless steelDialgalvanic blue

Reference/Strap 1-65-01-29-15-30 (Louisiana Alligator leather strap black)

1-65-01-29-15-31 (Louisiana Alligator nubuck leather strap black)

Case material 18 ct red gold

Dial galvanic black

Case diameter40 mmHeight11.7 mmStrap20/18 mm

Water proof up to 5 bar

Glass sapphire crystal, on both sides anti-reflective

Bottom sapphire crystal

Calibre Manual winding movement, Calibre 65-01

Dimenions Diameter 32.2 mm, height 6.1 mm

Oscillation frequency 28,800 vph, equivalent to 4 Hz

Power reserve 42 hours (+/- 5%)

Jewels 48 (four of them in screwed and one in pressed gold chatons)

Balance screw balance with 18 weighted screws





Page 2

Additional details

Hours and minutes (off-centre), small second (off-centre), Panorama Date, power reserve display (retrograde), second stop; exquisitely finished movement, beveled/polished edges, polished and brushed steel parts, blued screws, screwed gold chatons, hand engraved balance bridge and second cock, Glashütte three-quarter plate with stripe finish, duplex swanneck fine adjustment.

